Superior vinyl

Durability

Freedom from wear

Heat/cold resistance

Highest consumer satisfaction

Victorian Patio Door Series



Features



The Victorian Patio Door **Performance Series** is manufactured from the most advanced vinyl. A high-grade resin recipe unmatched for strength and freedom from wear. Offering beauty and performance – it will not rot, rust, pit or blister over long periods of time.

Our multi-chambered, allvinyl frame is durable and easy to install. Maximized strength withstands high winds and provides superior air tightness. **Sunview** Patio Doors are ideal for new construction and available with the highest quality accessories and upgrades including security, colour and finishing options. Our goal – the highest buyer satisfaction.

Optional

Frame & Sash

Raise

lever

and lower operation

- 11/4", 2", or 33/8"
- frame extensions
- 4_{1/2}" sill plate
- Brick mold • Sill extensions

Optional Hardware

These unique handle sets can be configured with single-point or heavy duty multi-point keylocks and are available in White, Black, Brass, Black Nickel, Satin Nickel or Bright Chrome.



Optional Internal Mini-Blinds

- Fingertip operation
- No external cords
- No dusting
- Low-E glass

Maximum visibility to complete privacy at the tip of a finger. The lever raises, lowers or tilts the blinds sealed between the insulated glass to ensure maintenance-free operation.



Optional Decorative Grills

Internal grills are available in a wide range of design styles with colours that include Flat Grills in Two-tone, White, Brass and Pewter, Georgian Grills in White, and Pencil Grills in White, Brass and Pewter.

Vinyl Frame

- 57/8" mechanically fastened vinyl frame
- Components easily installed and replaceable
- 3 weather seals
- Anodized screen track/stainless steel roller track
- 8 degree sill slope for optimal drainage

Durable Sash

- Reinforced with steel to withstand high wind loads
- Double perimeter seal for superior air-tightness
- Doors are easily and completely reversible
- Adjustable nylon tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance

Stays cool in summer Glazing

Enhancing the outstanding thermal efficiency is the 1" high-performance glazing found in Cardinal[®] Low-E glass and Edgetech Super Spacer® technology. Super Spacer® Stays warm in winter

Hardware & Glass Options









Two Position Kick Locks mount on the bottom of the operating door. Used as secondary lock. Available in white, beige or brown.

Guardian Locks mount on the top of the operating door: security bolt locks into the frame. Available in white, beige or brown.

Folding Security Bars mount on the fixed side of the door frame and swing down to stop the door from operating.








Optional Exterior Colours

Sunview Patio Doors boast a wide range of colour options that feature a finish which is U.V. stable, has a superior adhesion process and is impact

resistant.


Specifications


Dimensions Door/Panel Configurations and Finished Sizes (Exterior view)







XO-Slide Right





OXO-Slide R to L or





OXXO-Slide R and Slide L from Centre

	No Slue Right	0Z0-Slide L to R			
2 Panels		3 Panels		4 Panels	
58 1/2 W	х 79 1/2 Н	88 3/4 W	х 79 1/2 Н	117 1/8 W x	79 1/2 H
59 1/2 W	х 79 1/2 Н	88 3/4 W	x 81 1/2 H	117 1/8 W X	81 1/2 H
59 1/2 W	x 81 1/2 H	88 3/4 W	х 95 1/2 Н	117 1/8 W x	95 1/2 H
59 1/2 W	x 95 1/2 H	106 3/4 W	/ x 79 1/2 H	141 _{1/8} W x	
70 1/2 W	х 79 1/2 Н				
71 1/2 W	x 79 1/2 H	1063/4 1	/ x 81 1/2 H	141 _{1/8} W x	8 1/2 H
71 1/2 W	x 81 1/2 H	106 3/4 W	/ x 95 1/2 H	141 1/8 W X	95 1/2 H
71 1/2 W	х 95 1/2 Н	142 3/4 W	/ x 79 1/2 H	189 1/8 W X	79 1/2 H
95 1/2 W	х 791/2 Н	142 3/4 W	/ x 81 1/2 H	189 _{1/8} W x	81 1/2 H
95 1/2 W	x 811/2 H	142 3/4 W	/ x 95 1/2 H	189 1/8 W X	95 1/2 H
95 1/2 W	х 95 1/2 Н	••••			

Performance Victorian Patio Door Series meet or exceed the specifications of CAN/CGSB-82.1-M89

Canadian Standards	Air Tightness	Water Tightness	Wind Load Resistance	
CAN/CGSB-82-1-M89	A3	В4	C3	
AAMA/WDMA/CSA 101/1.S.2/A440-08	Passed	DP55	DP55	MAA National Ferentration Reting Council®

Distributed By:

Our products meet the Energy Star program guidelines for helping businesses and individuals protect the environment through superior energy efficiency.

