

## AWNING





# Awning

**Vinyl-Pro's awning windows can be installed stand-alone to create a dramatic effect.**

They can also be used in combination with our fixed windows to build a truly graceful picture window. Our awning windows have the same energy-saving properties and quality features as much as our Casement windows.



<p><b>Canada</b></p>  <p><b>ENERGY STAR</b></p> <p>For more info call 1-888-205-8026</p>	<p>Qualified for <b>highlighted</b> area. Répond aux exigences pour les régions <b>indiquées</b>.</p>  <p>Zone A Zone B Zone C</p>		<p>Canada • Zone</p>
<p><b>U-Factor</b> 1.172</p> <p><b>Energy Rating</b> +36</p>	<p><b>Solar Heat Gain Co-efficient</b> 0.388</p> <p><b>Air Leakage</b> 0.141</p> <p>CSA A440-00 A3B7C5S1F10</p>	<p><b>Visual Transmittance</b> 0.40</p>	



## A CLOSER LOOK OF VINYL CONSTRUCTION

Vinyl-Pro windows are made from an exclusive, 100% uPVC powder compound that is entirely lead-free. This special compound gives the system a better resistance to impact and discoloration. The windows are maintenance-free and will not crack, blister or warp.

*These windows have the highest number of internal air chambers, giving them outstanding insulation and sound abatement qualities, as well as thermal efficiency and increased sturdiness.*

### Jamb extension

*A choice of maintenance-free PVC jamb extensions, frame moldings and corner blocks are available to enhance inside finishing.*

### Corner block

*Fusion welding Corners provide attractive appearance & eliminate the need for adhesive and sealants. There are no imperfections on the completely watertight and airtight surface. Internal walls are also welded for increased overall structural strength.*

### Inside trim

### Additional Features

- Opening mechanism and high-security multipoint locking system come with stainless steel hinges and tracks.
- Hardware mounting is done through a minimum of two uPVC frame walls for secure and durable fastening.
- Depending on the model, casements open at a full 90°.

*Sealed glass unit has 13/16" overall thickness. Depending on the model, glazing of different types and thicknesses can be applied, including single, double, triple and Low-E glazing as well as a glazed decorative panel (3/4" to 1-1/8")*

